



Smart Node

Discover the Joy of Smart Living

Datasheet

Curtain Flow



Control with...



Alexa



Google Home



Android



iOS




1ch Remote



2ch. Remote



16ch. Remote



Product features

- ▶ Supports Arabian and three-pleat curtains
- ▶ Supports of straight and curved track
- ▶ Supports three styles of draw
 1. Center opening
 2. Left side opening
 3. Right side opening
- ▶ Supports ceiling and wall mount fitting
- ▶ Supports manual operation for opening or closing the curtain
- ▶ Supports auto-cut-off on overload
- ▶ Supports electronic limits with auto-calibration
- ▶ Supports up to 30 feet of track

- ▶ Comes with controllable speed
- ▶ Supports a smooth start and stop
- ▶ Supports up to 16-ch RF remote
- ▶ 10 RF remotes can be "learned or saved" in a single curtain motor
- ▶ The RF remote long press supports predefined locations (1/4, 2/4, and 3/4 lengths)
- ▶ A maximum of 25 schedules can be created
- ▶ Go to a specific location after a predefined time duration is supported (auto-restore location)
- ▶ Real time Feedback

Technical Specifications

Operating voltage	100 - 240 VAC
Frequency range	50/60Hz
Rated speed	Adj on
Rated power	15W
Wireless connection	2.4 GHz
Control mode	SmartNode app, Touch control, Rocker switches, RF Remote and WT
App support	Android/iOS
Item size	60*50*300 mm(L*W*H)
No. of wires	5
Technology	Wi-Fi
Safety curtain weight	50Kg
Remote communication	RF
Air humidity	< 85% non-condensing
Operational temperature range	-10 ...+50°C
Storage temperature range	-20...+50°C
Transport temperature range	-25...+75°C
Noise	40db
Rated torque	1.8Nm
Running speed	16cm/s*
RF frequency	433.92 MHz
No. of phase	Single

*Depends on Load

Product Diagram

